



## LinearTube™

### LINEARTUBE™ 30W IP69K IK10 1200MM LED ANTI-CORROSIVE 4000K

- High-Efficiency (150 lm/W) IP69K Corrosion-Resistant Linear Batten with opal UV-resistant polycarbonate diffuser, IK10 rated for maximum impact resistance.
- IP69K rated and designed for environments requiring heavy wash-down cleaning.
- Supplied with 316 stainless steel end-caps and mounting brackets for simplified surface installation.
- Integrated flicker-free, non-dimmable driver with IP69K cable glands on both ends and 3pol push terminals for safe, rapid through-wiring.
- UV resistant and suitable for installations in unprotected outdoor areas with ambient temperatures from -20 °C to +45 °C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>AC153250</b>	Non-Dimmable	4000K	30W	4500lm	150lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## LinearTube™

### LINEARTUBE™ 30W IP69K IK10 1200MM LED ANTI-CORROSIVE 4000K

#### Specifications and Benefits

Ingress Protection Rating	IP69k
IK Rating	IK10
Operating Temperature Range	-25°C / +45°C
Mounting Type	Surface mounted / Wall mounted
Positional Adjustment	Fixed
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Indoor / Outdoor
Body Material	PC
Cover Material	PC
Finishing	White

#### Technical Specifications

Wattage	30W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>200,000
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Energy Rating	D
Inrush Current	25A/280µs

#### Photometric Specifications

Lumens	4500lm
Efficiency	Up to 150lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
Beam Angle	120°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640153250
Product Weight	850g
Product Dimensions (ODxH / LxWxH)	Ø73 xmm
Boxed Product Weight	1600g
Boxed Product Dimensions (LxWxH)	1260 x 80 x 80mm
Outer Carton Boxed Product Quantity	4 pcs
Outer Carton Dimensions (LxWxH)	1275 x 175 x 180mm

