



## OrbitalCSR™

### ORBITALCSR™ D360 COLOUR & WATTAGE SWITCHABLE CSR IP66 BULKHEAD 3000K/3500/4000K MS SENSOR

- Colour & Wattage Switchable IP66 Modular Plug&Play Bulkhead with opal polycarbonate IK10 diffuser for even and uniform light distribution.
- Designed for modular plug and play product extension and maintenance. Plug-ready sensors, emergency kit, maintainable driver and light-engine available.
- Integrated sensor base enables tool-free upgrade with either a microwave sensor for motion detection or a microwave sensor with corridor function for presence, daylight harvesting, and configurable hold time and light output control. 108° detection range up to 4 m.
- IP66 rated rear and side entry access wiring compartment enable quick and simple through-wiring and product installation.
- UV resistant and suitable for installations in unprotected outdoor areas with ambient temperatures from -25°C to +45°C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>BH150358</b>	Microwave Sensor	3000 / 3500 / 4000K	15 / 22 / 28W	1500-3360lm	Up to 120lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## OrbitalCSR™

### ORBITALCSR™ D360 COLOUR & WATTAGE SWITCHABLE CSR IP66 BULKHEAD 3000K/3500/4000K MS SENSOR

#### Specifications and Benefits

Ingress Protection Rating	IP66
IK Rating	IK10
Operating Temperature Range	-25°C / +45°C
Mounting Type	Surface mounted / Wall mounted
Positional Adjustment	Fixed
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor / Outdoor
Body Material	Plastic
Cover Material	PC
Finishing	White

#### Technical Specifications

Wattage	15/22/28
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>25,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Energy Rating	D
Inrush Current	10A

#### Photometric Specifications

Lumens	15W - 1500 / 1800 / 1650lm 22W - 2200 / 2640 / 2420lm 28W - 2800 / 3360 / 3080lm
Efficiency	Up to 120lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	120°
CRI	>80
Dimming Type	Microwave Sensor
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640150358
Product Weight	1320g
Product Dimensions (ODxH / LxWxH)	Ø360 x 105mm
Boxed Product Weight	1620g
Boxed Product Dimensions (LxWxH)	362 x 362 x 107mm
Outer Carton Boxed Product Quantity	10 pcs
Outer Carton Dimensions (LxWxH)	740 x 550 x 375mm

