


Spherical™

SPHERAL™ 18W IP65 LED BULKHEAD WHITE 4000K

- IP65 18W Bulkhead with opal polycarbonate IK10 diffuser for even and uniform light distribution offer best value for money.
- IP65 rated rear and side entry access wiring compartment enable quick and simple through-wiring and product installation.
- Microwave Sensor version with daylight harvesting feature, 110° detection range up to 4 meter and adjustable hold time configurations from 5 seconds to 30 minutes available.
- UV resistant and suitable for installations in unprotected outdoor areas with ambient temperatures from -25°C to +45°C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
BH150426	Non-Dimmable	4000K	18W	1899lm	105lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

Spherical™

SPHERAL™ 18W IP65 LED BULKHEAD WHITE 4000K

Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK10
Operating Temperature Range	-25°C / +45°C
Mounting Type	Surface mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor / Outdoor
Body Material	Plastic
Cover Material	PC
Finishing	White
Available accessories	N/A

Technical Specifications

Wattage	18W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>25,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Energy Rating	D
Inrush Current	10A

Photometric Specifications

Lumens	1899lm
Efficiency	Up to 105lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
Beam Angle	120°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640150426
Product Weight	860g
Product Dimensions (ODxH / LxWxH)	Ø330 x 78mm
Boxed Product Weight	950g
Boxed Product Dimensions (LxWxH)	333 x 333 x 80mm
Outer Carton Boxed Product Quantity	10 pcs
Outer Carton Dimensions (LxWxH)	695 x 360 x 425mm

