



UtiliteCS™

UTILITECS™ 15W POLYCARBONATE IP65 ROUND LED BULKHEAD 3CCT 3000K/4000K/6500K

- Colour Switchable IP65 Round Bulkhead with opal polycarbonate IK06 diffuser offer best value for money solution.
- IP65 rated rear and side entry access wiring compartment enable quick and simple through-wiring and product installation.
- Colour switchable between 3000K, 4000K & 6500K.
- Suitable for ambient temperatures from -20°C to +40°C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
BH156831	Non-Dimmable	3000 / 4000 / 6500K	15W	1500-1650lm	Up to 110lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

UtiliteCS™

UTILITECS™ 15W POLYCARBONATE IP65 ROUND LED BULKHEAD 3CCT 3000K/4000K/6500K

Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK06
Operating Temperature Range	-20°C / +40°C
Mounting Type	Surface mounted / Wall mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor / Outdoor
Body Material	Plastic
Cover Material	PC
Finishing	White
Available accessories	N/A

Technical Specifications

Wattage	15W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.5
Switching Cycles	>100,000
Lifetime Hours	L70 B50 25,000hrs L80 B20 15,000hrs
Energy Rating	D
Insulation Coverable	N/A
Inrush Current	9A

Photometric Specifications

Lumens	1500 / 1650 / 1550lm
Efficiency	Up to 110lm/W
Colour Temperature	3000 / 4000 / 6500K
Light Colour Definition	Switchable White
Beam Angle	120°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640156831
Product Weight	198g
Product Dimensions (ODxH / LxWxH)	Ø167 x 62mm
Boxed Product Weight	256g
Boxed Product Dimensions (LxWxH)	70 x 65 x 70mm
Outer Carton Boxed Product Quantity	10 pcs
Outer Carton Dimensions (LxWxH)	360 x 205 x 253mm

