


LinoraCS[™]

MAGNETIC UP LIGHT 30% FOR LINORA CS[™] REFLECTOR CUP VERSION

Code	Version	Colour	Watts	lm/W	CRI
CL163730	Non-Dimmable	3000 / 3500 / 4000K	8.5W	130lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

LinoraCS™

MAGNETIC UP LIGHT 30% FOR LINORA CS™ REFLECTOR CUP VERSION

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK02
Operating Temperature Range	-20°C / +40°C
Mounting Type	Surface mounted / Magnetic
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class III
Installation Location	Indoor
Body Material	PC
Cover Material	PC
Available accessories	N/A

Technical Specifications

Wattage	8.5W
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>25,000
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Insulation Coverable	NO

Photometric Specifications

Efficiency	Up to 130lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
Beam Angle	115°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640163730
Product Weight	110g
Product Dimensions (ODxH / LxWxH)	730 x 20 x 9mm
Boxed Product Weight	120g
Boxed Product Dimensions (LxWxH)	730 x 20 x 9mm
Outer Carton Boxed Product Quantity	50 pcs
Outer Carton Dimensions (LxWxH)	750 x 350 x 215mm

