



## LenoWS™

### LENOWS™ TRACK LINEAR 577MM WATTAGE SWITCHABLE SINGLE COLOUR 4000K WHITE FINISH 90° BEAM ANGLE

- Wattage Switchable In-Track Linear Luminaire designed for use with existing 3-circuit track systems, providing ultimate flexibility for retail and commercial environments.
- Slim-profile in-track adapter with integrated phase-change feature and wattage dip switch.
- Innovative optical lens pattern delivers market-leading efficiency of up to 175 lm/W with beam angle of 90°.
- Customization options available in black or silver finish, wide range of beam angles, colour temperatures and food-specific CCT rendering.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>CL164027</b>	Non-Dimmable	4000K	14 / 17 / 20 / 24W	2350-3950lm	Up to 167lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

# LenoWS™

## LENOWS™ TRACK LINEAR 577MM WATTAGE SWITCHABLE SINGLE COLOUR 4000K WHITE FINISH 90° BEAM ANGLE

### Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK04
Operating Temperature Range	-20°C / +45°C
Mounting Type	3-circuit track
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PMMA
Available accessories	N/A

### Technical Specifications

Wattage	14/17/20/24
Nominal Voltage	200-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>50,000
Lifetime Hours	L70 B50 110,000hrs L80 B20 104,000hrs
Inrush Current	12.65A/276us

### Photometric Specifications

Lumens	14W 2350lm 17W 2850lm 20W 3350lm 24W 3950lm
Efficiency	Up to 167lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
Beam Angle	90°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

### Logistic Details

EAN / Barcode	3609640164027
Product Weight	710g
Product Dimensions (ODxH / LxWxH)	578 x 64 x 55.5mm
Boxed Product Weight	800g
Boxed Product Dimensions (LxWxH)	586 x 74 x 74mm
Outer Carton Boxed Product Quantity	6 pcs
Outer Carton Dimensions (LxWxH)	605 x 245 x 170mm

