



LivoCS™

COLOUR SWITCHABLE LINEAR LIGHT SURFACE/SUSPENSION REFLECTOR CUP + LENSE 1500MM WHITE

- Modular, Colour Switchable Linear Luminaire with superior finish, durable steel body, and a high-efficiency, UGR16 low, glare reflector cup and lens optics.
- Tool-free rapid connection system with integrated plug-and-play electrical connection enables fully modular, quick, and flexible installations — ideal for suspended and surface-mounted applications in commercial environments.
- Colour-switchable between 3000K / 3500K / 4000K via an easy-access dip switch on the side of the luminaire, offering maximum flexibility.
- Optional tool-free up-light module provides a 30% up-light / 70% down-light distribution, enhancing ambient lighting and promoting well-being in any environment.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
CL164072	Non-Dimmable	3000 / 3500 / 4000K	40W	5600-6400lm	Up to 160lm/W	16	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

LivoCS™

COLOUR SWITCHABLE LINEAR LIGHT SURFACE/SUSPENSION REFLECTOR CUP + LENSE 1500MM WHITE

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK05
Operating Temperature Range	-20°C / +40°C
Mounting Type	Surface mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PMMA
Available accessories	N/A

Technical Specifications

Wattage	40W
Nominal Voltage	200-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>25,000
Lifetime Hours	L70 B50 110,000hrs L80 B20 72,000hrs
Energy Rating	C
Insulation Coverable	NO
Inrush Current	14.125A/272us

Photometric Specifications

Lumens	4600 / 6400 / 6000lm
Efficiency	Up to 160lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<3
Beam Angle	75°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640164072
Product Weight	6150g
Product Dimensions (ODxH / LxWxH)	1500 x 160 x 40mm
Boxed Product Weight	7000g
Boxed Product Dimensions (LxWxH)	1535 x 60 x 190mm
Outer Carton Boxed Product Quantity	4 pcs
Outer Carton Dimensions (LxWxH)	1555 x 280 x 210mm

