



PATHWAYCS™

8W COLOUR SWITCHABLE BOLLARD LIGHT Ø100XH750MM + HEAD 125MM

- Colour Switchable IP65 Bollard anthracite black cast aluminium housing — the perfect choice for residential environments.
- Durable corrosion, high-impact and salt-spray resistant housing with integrated triac dimmable driver and IP68 waterproof junction box for simplified and reliable through-wiring installation.
- Bollard head with 360° beam angle and optical performance design deliver a very low ULR value of 3.5 reducing light pollution.
- Colour Switchable between 3000K and 4000K.
- Suitable for ambient temperature -20°C to +45°C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
DC162221	Non-Dimmable	3000 / 4000K	8W	430-530lm	Up to 63lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

PATHWAYCS™

8W COLOUR SWITCHABLE BOLLARD LIGHT Ø100XH750MM + HEAD 125MM

Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK08
Operating Temperature Range	-20°C / +45°C
Mounting Type	Surface mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Outdoor
Body Material	Aluminium
Cover Material	PC
Available accessories	N/A

Technical Specifications

Wattage	8W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.88
Switching Cycles	>100,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Inrush Current	3.44A/48.4uS

Photometric Specifications

Efficiency	Up to 63lm/W
Colour Temperature	3000K
Light Colour Definition	Switchable White
Beam Angle	360°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Indirect

Logistic Details

EAN / Barcode	3609640162221
Product Weight	1800g
Product Dimensions (ODxH / LxWxH)	Ø100 x 750mm
Boxed Product Weight	2500g
Boxed Product Dimensions (LxWxH)	167 x 145 x 785mm
Outer Carton Boxed Product Quantity	6 pcs
Outer Carton Dimensions (LxWxH)	800 x 515 x 310mm

