



ISOPRO™

ISOPRO™ FIXED IP65 5W GU10 COVERABLE RECESSED DOWNLIGHT PACK WHITE 3000K

- IP65/IP50 GU10 Universal Downlight including GU10 socket and lamp and Fixed Aluminium Bezel in White. Designed to seal ceilings completely.
- Rapid installation through loop in/loop out push-fit wiring terminals with strain relief.
- Fully insulation coverable (blown or unwound) without the need of additional accessory or insulation cut-out. Vapour-barrier compatible.
- ISOPRO Kit includes the GU10 ICE lamp with superior thermal management which has been specifically designed and tested in fully enclosed insulation coverable downlights.
- Airtight and Acoustics rated.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
DL150037	Non-Dimmable	3000K	5W	500lm	100lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ISOPRO™

ISOPRO™ FIXED IP65 5W GU10 COVERABLE RECESSED DOWNLIGHT PACK WHITE 3000K

Specifications and Benefits

Ingress Protection Rating	IP65
Operating Temperature Range	-20°C / +40°C
Mounting Type	Recessed
Cutout Dimension	min: 75mm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Steel
Cover Material	Glass
Finishing	White
Available accessories	N/A

Technical Specifications

Wattage	5W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.5
Switching Cycles	>25,000
Lifetime Hours	L70 B50 25,000hrs L80 B20 15,000hrs
Insulation Coverable	YES

Photometric Specifications

Lumens	500lm
Efficiency	Up to 100lm/W
Colour Temperature	3000K
Light Colour Definition	Warm White
SDCM	<4
Beam Angle	60°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640150037
Product Weight	269g
Product Dimensions (ODxH / LxWxH)	Ø90 x 84mm
Recess Depth	84mm
Boxed Product Weight	326g
Boxed Product Dimensions (LxWxH)	175 x 95 x 100mm
Outer Carton Boxed Product Quantity	20 pcs
Outer Carton Dimensions (LxWxH)	495 x 365 x 219mm

