



ISOPRO™

ISOPRO™ FIXED IP65 5W GU10 COVERABLE RECESSED DOWNLIGHT PACK WHITE 4000K

- IP65/IP50 GU10 Universal Downlight including GU10 socket and lamp and Fixed Aluminium Bezel in White. Designed to seal ceilings completely.
- Rapid installation through loop in/loop out push-fit wiring terminals with strain relief.
- Fully insulation coverable (blown or unwound) without the need of additional accessory or insulation cut-out. Vapour-barrier compatible.
- ISOPRO Kit includes the GU10 ICE lamp with superior thermal management which has been specifically designed and tested in fully enclosed insulation coverable downlights.
- Airtight and Acoustics rated.

| Code | Version | Colour | Watts | Lumens | lm/W | CRI |
|-----------------|--------------|--------|-------|--------|---------|-----|
| DL150044 | Non-Dimmable | 4000K | 5W | 520lm | 104lm/W | 80 |



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ISOPRO™

ISOPRO™ FIXED IP65 5W GU10 COVERABLE RECESSED DOWNLIGHT PACK WHITE 4000K

Specifications and Benefits

| | |
|-----------------------------|---------------------|
| Ingress Protection Rating | IP65 |
| Operating Temperature Range | -20°C / +40°C |
| Mounting Type | Recessed |
| Cutout Dimension | min: 75mm - max: mm |
| Certification | CE |
| Protection Class | Class I |
| Installation Location | Indoor |
| Body Material | Steel |
| Cover Material | Glass |
| Finishing | White |
| Available accessories | N/A |

Technical Specifications

| | |
|----------------------|--|
| Wattage | 5W |
| Nominal Voltage | 220-240Vac |
| Frequency | 50/60Hz |
| Power Factor | >0.5 |
| Switching Cycles | >25,000 |
| Lifetime Hours | L70 B50 25,000hrs L80 B20 15,000hrs |
| Insulation Coverable | YES |

Photometric Specifications

| | |
|-------------------------|---------------|
| Lumens | 520lm |
| Efficiency | Up to 104lm/W |
| Colour Temperature | 4000K |
| Light Colour Definition | Neutral White |
| SDCM | <4 |
| Beam Angle | 60° |
| CRI | >80 |
| Dimming Type | Non-Dimmable |
| Distribution | Direct |

Logistic Details

| | |
|-------------------------------------|-------------------|
| EAN / Barcode | 3609640150044 |
| Product Weight | 269g |
| Product Dimensions (ODxH / LxWxH) | Ø90 x 84mm |
| Recess Depth | 84mm |
| Boxed Product Weight | 326g |
| Boxed Product Dimensions (LxWxH) | 175 x 95 x 100mm |
| Outer Carton Boxed Product Quantity | 20 pcs |
| Outer Carton Dimensions (LxWxH) | 495 x 365 x 219mm |

