



ISOPRO™

ISOPRO™ FIXED IP65 5W DIMMABLE GU10 COVERABLE RECESSED DOWNLIGHT PACK WHITE 4000K

- IP65/IP50 GU10 Universal Downlight including GU10 socket and lamp and Fixed Aluminium Bezel in White. Designed to seal ceilings completely.
- Rapid installation through loop in/loop out push-fit wiring terminals with strain relief.
- Fully insulation coverable (blown or unwound) without the need of additional accessory or insulation cut-out. Vapour-barrier compatible.
- ISOPRO Kit includes the GU10 ICE lamp with superior thermal management which has been specifically designed and tested in fully enclosed insulation coverable downlights.
- Airtight and Acoustics rated.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
DL150082	Dimmable	4000K	5W	520lm	104lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ISOPRO[™]PROKIT

ISOPRO[™] FIXED IP65 5W DIMMABLE GU10 COVERABLE RECESSED DOWNLIGHT PACK WHITE 4000K

Specifications and Benefits

Ingress Protection Rating	IP65
Operating Temperature Range	-20°C / +40°C
Mounting Type	Recessed
Cutout Dimension	min: 75mm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Steel
Cover Material	Glass
Finishing	White
Available accessories	N/A

Technical Specifications

Wattage	5W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.5
Switching Cycles	>25,000
Lifetime Hours	L70 B50 25,000hrs L80 B20 15,000hrs
Insulation Coverable	YES

Photometric Specifications

Lumens	520lm
Efficiency	Up to 104lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<4
Beam Angle	60°
CRI	>80
Dimming Type	Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640150082
Product Weight	279g
Product Dimensions (ODxH / LxWxH)	Ø90 x 84mm
Recess Depth	84mm
Boxed Product Weight	337g
Boxed Product Dimensions (LxWxH)	175 x 95 x 100mm
Outer Carton Boxed Product Quantity	20 pcs
Outer Carton Dimensions (LxWxH)	495 x 365 x 219mm

