



Slim-FitCS™

SLIM-FIT CS™ 6W IP44 ROUND LOW PROFILE LED DOWNLIGHT 2CCT 3000/4000K

- Colour Switchable super-slim Aluminium edge-lite low profile LED Downlights are ideal for installations in limited recess space (23mm including driver).
- Wide product range covers most common cut-out dimensions of traditional light sources and delivers enhanced energy savings.
- PMMA light guide with PC diffuser for low glare even light distribution.
- Supplied with remote non-dimmable constant current driver and 150mm cable for ease of installation.
- Dimmable driver options as accessory.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
DL150235	Non-Dimmable	3000 / 4000K	6W	475-500lm	Up to 83lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

Slim-FitCS™

SLIM-FIT CS™ 6W IP44 ROUND LOW PROFILE LED DOWNLIGHT 2CCT 3000/4000K

Specifications and Benefits

Ingress Protection Rating	IP44
IK Rating	IK04
Operating Temperature Range	-20°C / +50°C
Mounting Type	Recessed
Positional Adjustment	Fixed
Cutout Dimension	min: 105mm - max: 110mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PS
Finishing	White

Technical Specifications

Wattage	6W
Nominal Voltage	200-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>100,000
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Energy Rating	D
Insulation Coverable	NO

Photometric Specifications

Efficiency	Up to 83lm/W
Colour Temperature	3000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	110°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640150235
Product Weight	180g
Product Dimensions (ODxH / LxWxH)	Ø120 x 25mm
Recess Depth	23mm
Boxed Product Weight	220g
Boxed Product Dimensions (LxWxH)	155 x 125 x 35mm
Outer Carton Boxed Product Quantity	40 pcs
Outer Carton Dimensions (LxWxH)	330 x 380 x 265mm

