



PavoCWS™

PAVOCWS™ 12/18/24W LED NON-DIM ADJUSTABLE SURFACE/RECESSED DOWNLIGHT 3CCT WITH MS SENSOR

- Colour & Wattage Switchable Polycarbonate LED Downlight for surface or recessed installations with adjustable cut-out.
- 3 Wattage and 3 Colour Selections available for ultimate flexibility in every application and perfect retrofit solution for renovations.
- One size fit all bracket for adjustable cut-out between 65-180mm (DL149529 & DL151133) or 65-240mm (DL150389 & DL151140) enables flexible recessed or surface mount installation.
- Integrated non dimmable led driver for very low profile installation height of only 17mm.
- Magnetic design allows customization of white standard version with magnetic Black and Satin Nickel bezels.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
DL151140	Non-Dimmable	3000 / 4000 / 6000K	12 / 18 / 24W	900-1920lm	Up to 85lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

PavoCWS™

PAVOCWS™ 12/18/24W LED NON-DIM ADJUSTABLE SURFACE/RECESSED DOWNLIGHT 3CCT WITH MS SENSOR

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK05
Operating Temperature Range	-10°C / +45°C
Mounting Type	Surface mounted / Semi-recessed
Positional Adjustment	Rotatable
Cutout Dimension	min: 65mm - max: 240mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Plastic
Cover Material	PC
Finishing	White

Technical Specifications

Wattage	12/18/24
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.7
Switching Cycles	>25,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Energy Rating	F
Insulation Coverable	NO

Photometric Specifications

Lumens	12W - 900 / 1030 / 900lm 18W - 1350 / 1440 / 1500lm 24W - 1800 / 2000 / 1800lm
Efficiency	Up to 85lm/W
Colour Temperature	3000 / 4000 / 6000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	120°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640151140
Product Weight	583g
Product Dimensions (ODxH / LxWxH)	Ø300 x 17mm
Recess Depth	17mm
Boxed Product Weight	759g
Boxed Product Dimensions (LxWxH)	31 x 305 x 300mm
Outer Carton Boxed Product Quantity	10 pcs
Outer Carton Dimensions (LxWxH)	325 x 335 x 325mm

