



## PavoCWS PRO™

### PAVOCWS PRO™ 10/13/16W LED NON-DIM SURFACE/RECESSED DOWNLIGHT 3CCT 3000/4000/5700K

- Colour & Wattage Switchable Aluminium LED Downlight for surface or recessed installations with adjustable cut-out.
- 3 Wattage and 3 Colour Selections available for ultimate flexibility in every application and perfect retrofit solution for renovations.
- One size fit all bracket for adjustable cut-out between 65-205mm enables flexible recessed or surface mount installation.
- Integrated non dimmable led driver for very low profile installation height of only 16mm.
- Supplied with 300mm pre-wired cable for quick installation.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>DL151966</b>	Non-Dimmable	3000 / 4000 / 5700K	10 / 13 / 16W	940-1450lm	Up to 99lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## PavoCWS PRO™

### PAVOCWS PRO™ 10/13/16W LED NON-DIM SURFACE/RECESSED DOWNLIGHT 3CCT 3000/4000/5700K

#### Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK05
Operating Temperature Range	-20°C / +45°C
Mounting Type	Surface mounted / Semi-recessed
Cutout Dimension	min: 65mm - max: 205mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium, PC
Cover Material	PS
Finishing	White
Available accessories	N/A

#### Technical Specifications

Wattage	10/13/16
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>100,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Energy Rating	E
Insulation Coverable	NO

#### Photometric Specifications

Lumens	10W - 990 / 990 / 960lm 13W - 1190 / 1260 / 1200lm 16W - 1350 / 1450 / 1360lm
Efficiency	Up to 99lm/W
Colour Temperature	3000 / 4000 / 5700K
Light Colour Definition	Switchable White
Beam Angle	120°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640151966
Product Weight	470g
Product Dimensions (ODxH / LxWxH)	Ø235 x 16mm
Recess Depth	16mm
Boxed Product Weight	480g
Boxed Product Dimensions (LxWxH)	245 x 30 x 275mm
Outer Carton Boxed Product Quantity	20 pcs
Outer Carton Dimensions (LxWxH)	505 x 325 x 290mm

