




## ONExLITE™

### ONEXLITE™ IP65/IP50 COLOUR & WATTAGE SELECTABLE DIMMABLE LED ADJUSTABLE/FIXED DOWNLIGHT WITHOUT BEZEL

- Colour & Wattage Switchable Convertible Triac dimmable LED Downlight.
- Convertible IP65 Bezel design enables transformation from adjustable into fixed design for maximum versatility. Supplied without Bezel.
- Rapid tool-free installation through loop in / loop out push-fit wiring terminals with strain relief.
- Compact integrated low profile design with insulation cover allow for use in shallow voids up to 50mm. Downlight and driver are insulation coverable.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>DL159887</b>	Dimmable	2700 / 3000 / 4000K	3.5 / 5.5W	350-600lm	Up to 109lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## ONExLITE™

### ONEXLITE™ IP65/IP50 COLOUR & WATTAGE SELECTABLE DIMMABLE LED ADJUSTABLE/FIXED DOWNLIGHT WITHOUT BEZEL

#### Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK04
Operating Temperature Range	-20°C / +45°C
Mounting Type	Recessed
Positional Adjustment	Swivelling
Cutout Dimension	min: 68mm - max: mm
Certification	CE
Protection Class	Class III
Installation Location	Indoor
Body Material	Steel, PC
Cover Material	PC
Finishing	White

#### Technical Specifications

Wattage	3,5/5,5
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.85
Switching Cycles	>100,000
Lifetime Hours	L70 B20 72,000hrs L80 B20 50,000hrs
Energy Rating	E
Insulation Coverable	YES
Inrush Current	1.9A

#### Photometric Specifications

Lumens	3.5W - / 370 / lm 5.5W - / 600 / lm
Efficiency	Up to 109lm/W
Colour Temperature	2700 / 3000 / 4000K
Light Colour Definition	Switchable White
SDCM	<4
Beam Angle	60°
CRI	>80
Dimming Type	Dimmable
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640159887
Product Weight	201g
Product Dimensions (ODxH / LxWxH)	Ø80 x 50mm
Recess Depth	50mm
Boxed Product Weight	231g
Boxed Product Dimensions (LxWxH)	125 x 85 x 95mm
Outer Carton Boxed Product Quantity	20 pcs
Outer Carton Dimensions (LxWxH)	445 x 275 x 215mm

