



ZYLO™

Ø115MM 27W IP54 SURFACE MOUNT DOWNLIGHT 3000K

- High-Quality Round Fixed Low-Luminance Surface-Mounted Ceiling Light featuring a white cast aluminium frame with onyx-colored reflector.
- Durable and versatile: Class II, IP54-rated, suitable for a wide range of environments.
- Excellent light quality with CRI 90, SDCM <3, and UGR <19 for consistent, comfortable illumination.
- Durable and versatile: Class II, IP54-rated, suitable for a wide range of environments.
- Two wattage options (10W and 27W) provide flexibility for different ceiling height.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
DL164133	Non-Dimmable	3000K	27W	2600lm	95lm/W	19	90



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ZYLO™

Ø115MM 27W IP54 SURFACE MOUNT DOWNLIGHT 3000K

Specifications and Benefits

Ingress Protection Rating	IP54
IK Rating	IK02
Operating Temperature Range	-10°C / +40°C
Mounting Type	Surface mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PC
Available accessories	N/A

Technical Specifications

Wattage	27W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>10,000
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Energy Rating	E
Insulation Coverable	NO
Inrush Current	16.4A

Photometric Specifications

Lumens	2600lm
Efficiency	Up to 95lm/W
Colour Temperature	3000K
Light Colour Definition	Warm White
SDCM	<3
Beam Angle	38°
CRI	>90
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640164133
Product Weight	780g
Product Dimensions (ODxH / LxWxH)	Ø115 x 152mm
Boxed Product Weight	800g
Boxed Product Dimensions (LxWxH)	135 x 135 x 163mm
Outer Carton Boxed Product Quantity	18 pcs
Outer Carton Dimensions (LxWxH)	420 x 285 x 505mm

