



## Slim-FitCS™

### SLIM-FIT CS™24W DIMMABLE DRIVER FOR DL150273

- The DR149666 driver is a phase cut dimmable driver. It is delivered pre-wired with 350 mm of 2-conductor cable on the primary side and a 1/2 connectorized cord for connection to the luminaire.
- Dimming range from 5-15 to 100% (minimum brightness may vary depending on the performance of the dimmer used).
- No flicker and smooth dimming in all light conditions.
- Leading and trailing edge compatible.

Code	Dimming	Input Voltage & Frequency	Output Voltage	Output Current	Protection Class
<b>DR149666</b>	Dimmable	200 - 240 VAC 50/60Hz	58 - 80 VDC	300mA	Class II



01/08/2025

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## Slim-FitCS<sup>™</sup>

### SLIM-FIT CS<sup>™</sup>24W DIMMABLE DRIVER FOR DL150273

Features	
Input Voltage	200 - 240 VAC
Output Voltage	58 - 80 VDC
Output Current	300mA
Electrical Protection Class	Class II
Dimming	Dimmable
Ingress Protection Rating	IP20
Operating Temperature	-20°C / 50°C
Case Temperature	75°C
Power Factor	>0,95

Logistic	
Product Height	43 mm
Product Width	43 mm
Product Length	150 mm
Product Weight	97 g
EAN	3609640149666

Compatible Products	
Slim-Fit CS <sup>™</sup> - DL150273	