




OrbitalCSR[™]

DRIVER FOR BH150341 & BH150358

- Driver for Modular Bulkhead OrbitalCSR BH150341 & BH150358.
- Output current adjustment (3 levels) using microswitches.

Code	Power	Dimming	Input Voltage & Frequency	Output Voltage	Output Current	Protection Class
DR159245	15 - 22 - 28W	Non-Dimma-ble	220 - 240 VAC 50/60Hz	60 - 120 VDC	170 - 310mA Maxi	Class II



01/08/2025

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

OrbitalCSR[™]

DRIVER FOR BH150341 & BH150358

Features	
Input Voltage	220 - 240 VAC
Output Voltage	60 - 120 VDC
Output Current	170 - 310mA Maxi
Power	15 - 22 - 28W
Electrical Protection Class	Class II
Dimming	Non-Dimmable
Ingress Protection Rating	IP20
Operating Temperature	-20°C / 50°C
Case Temperature	80°C
Power Factor	>0.95

Logistic	
Product Height	65 mm
Product Width	25 mm
Product Length	100 mm
Product Weight	52 g
EAN	3609640159245

Compatible Products	
OrbitalCSR [™] - BH150341	
OrbitalCSR [™] - BH150358	