



## Driver DALI™

### DALI PUSH DIM DRIVER (MAX 42W) FOR DL151065, LP149512 & LP149505 & LP154288 & LP155803

- The DR159429 driver is a dimmable DALI-2 and PushDIM driver with adjustable constant current. It is supplied complete with a cable for connection to the luminaire.
- Dimming range from 1 to 100%.
- No flicker and smooth dimming in all light conditions.
- Output current adjustment ( 10 levels ) by means of micro-switches.
- Support CBS , central emergency application.
- Independent cable clamps ( inlet / outlet ).

Code	Power	Dimming	Input Voltage & Frequency	Output Voltage	Output Current	Protection Class
<b>DR159429</b>	16 - 42W	DALI-2 / PUSH DIM	200 - 240 VAC/VDC 50/60Hz	6 - 42 VDC	450 - 1100mA Maxi	SELV Class II



01/08/2025

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## Driver DALI™

**DALI PUSH DIM DRIVER (MAX 42W) FOR DL151065, LP149512 & LP149505 & LP154288 & LP155803**

Features	
Input Voltage	200 - 240 VAC/VDC
Output Voltage	6 - 42 VDC
Output Current	450 - 1100mA Maxi
Power	16 - 42W
Electrical Protection Class	SELV Class II
Dimming	DALI-2 / PUSH DIM
Ingress Protection Rating	IP20
Operating Temperature	-20°C / 45°C
Case Temperature	90°C
Power Factor	>0.97
Input THD	<5%

Logistic	
Product Height	40 mm
Product Width	76 mm
Product Length	121 mm
Product Weight	173 g
EAN	3609640159429

01/08/2025