



VersiTile™

DALI PUSH DIM DRIVER (MAX 30W) FOR LP150280

- The DR159443 driver is a dimmable DALI-2 and PushDIM driver with adjustable constant current. It is supplied complete with a IP65 cable for connection to the luminaire.
- Dimming range from 1 to 100%.
- No flicker and smooth dimming in all light conditions.
- Output current adjustment (10 levels) by means of micro-switches.
- Support CBS , central emergency application.
- Independent cable clamps (inlet / outlet).

Code	Power	Dimming	Input Voltage & Frequency	Output Voltage	Output Current	Protection Class
DR159443	10 - 30W	DALI-2 Dimmable	200 - 240 VAC/VDC 50/60Hz	12 - 42 VDC	400 - 1100mA Maxi	SELV Class I



01/08/2025

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

VersiTile™

DALI PUSH DIM DRIVER (MAX 30W) FOR LP150280

Features	
Input Voltage	200 - 240 VAC/VDC
Output Voltage	12 - 42 VDC
Output Current	400 - 1100mA Maxi
Power	10 - 30W
Electrical Protection Class	SELV Class I
Dimming	DALI-2 Dimmable
Ingress Protection Rating	IP65
Operating Temperature	-20°C / 60°C
Case Temperature	90°C
Power Factor	>0.97
Input THD	<0.075%

Logistic	
Product Height	62 mm
Product Width	295 mm
Product Length	520 mm
Product Weight	480 g
EAN	3609640159443