



CosmosProWS

150W IP66 DALI DIMMABLE HIGHBAY 4000K

- Wattage Switchable Dali D4i High Power IK10 impact resistant IP66 LED Highbay with superior efficiency of up to 185lm/W.
- Interchangeable Lense design. Comes with 110° lense as standard, 90° lense options available as accessory.
- Integrated DALI D4i dimmable LED driver pre-wired with 1500mm cable/220mm dim wire for ease of installation. 800mm safety cable included.
- Zhaga base for plug and play Microwave or PIR Sensor Module with detection range up to 12m. Sensor options available as accessory.
- Suitable for -40° - +50° ambient working temperature.

Code	Colour	Watts	Lumens	lm/W	CRI
HB161392	4000K	120 / 150 / 200W	22200-37000lm	Up to 185lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

CosmosProWS™

150W IP66 DALI DIMMABLE HIGHBAY 4000K

Specifications and Benefits

Ingress Protection Rating	IP66
IK Rating	IK10
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Available accessories	N/A

Photometric Specifications

Lumens	120W 22200lm
	150W 27750lm
	200W 37000lm
Efficiency	Up to 185lm/W
Colour Temperature	4000K
Beam Angle	120°
CRI	>80

Technical Specifications

Wattage	120/150/200
Frequency	50/60Hz
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs

Logistic Details

EAN / Barcode	3609640161392
Product Dimensions (ODxH / LxWxH)	Ø331 x 140mm
Boxed Product Weight	0g
Outer Carton Boxed Product Quantity	0 pcs
Outer Carton Dimensions (LxWxH)	0 x 0 x 0mm

