



ICETMLAMP

ICETM 5W GU10 NON-DIMMABLE LED LAMP 3000K

- High efficiency and superior reliable GU10 lamp range.
- LEDchroic lens design with 60° beam angle imitates the appearance of halogen lamps and provides controlled, uniform light distribution with minimal glare.
- Superior thermal management to control LED and key component temperatures, potted driver to aid heat dissipation.
- Designed and tested for suitable use in enclosed fire rated and insulation coverable lighting fixture.
- Excellent dimming compatibility with all market common dimmers in Europe.

| Code | Version | Colour | Watts | Lumens | lm/W | Beam | CRI |
|-----------------|--------------|--------|-------|--------|---------|------|-----|
| LA149406 | Non-Dimmable | 3000K | 5W | 560lm | 112lm/W | 60° | 80 |



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ICE[™]LAMP

ICE[™] 5W GU10 NON-DIMMABLE LED LAMP 3000K

Specifications and Benefits

| | |
|-----------------------------|----------------------|
| Ingress Protection Rating | IP20 |
| Operating Temperature Range | -20°C / +40°C |
| Mounting Type | N/A |
| Cutout Dimension | min: N/Amm - max: mm |
| Certification | CE |
| Protection Class | Class II |
| Installation Location | Indoor |
| Body Material | Aluminium, PC |
| Finishing | White |
| Available accessories | N/A |

Photometric Specifications

| | |
|-------------------------|---------------|
| Lumens | 560lm |
| Efficiency | Up to 112lm/W |
| Colour Temperature | 3000K |
| Light Colour Definition | Warm White |
| SDCM | <6 |
| Beam Angle | 60° |
| CRI | >80 |
| Dimming Type | Non-Dimmable |
| Distribution | Direct |

Technical Specifications

| | |
|----------------------|--|
| Wattage | 5W |
| Nominal Voltage | 220-240Vac |
| Frequency | 50/60Hz |
| Power Factor | >0.5 |
| Switching Cycles | >15,000 |
| Lifetime Hours | L70 B20 25,000hrs L80 B20 15,000hrs |
| Energy Rating | E |
| Insulation Coverable | N/A |

Logistic Details

| | |
|-------------------------------------|-------------------|
| EAN / Barcode | 3609640149406 |
| Product Weight | 38g |
| Product Dimensions (ODxH / LxWxH) | Ø50 x 57mm |
| Boxed Product Weight | 55g |
| Boxed Product Dimensions (LxWxH) | 51 x 51 x 62mm |
| Outer Carton Boxed Product Quantity | 100 pcs |
| Outer Carton Dimensions (LxWxH) | 170 x 595 x 290mm |

