



# ICE<sup>TM</sup>LAMP

## ICE<sup>TM</sup> 5W GU10 DIMMABLE LED LAMP 4000K

- High efficiency and superior reliable GU10 lamp range.
- LEDchroic lens design with 60° beam angle imitates the appearance of halogen lamps and provides controlled, uniform light distribution with minimal glare.
- Superior thermal management to control LED and key component temperatures, potted driver to aid heat dissipation.
- Designed and tested for suitable use in enclosed fire rated and insulation coverable lighting fixture.
- Excellent dimming compatibility with all market common dimmers in Europe.

Code	Version	Colour	Watts	Lumens	lm/W	Beam	CRI
<b>LA149451</b>	Dimmable	4000K	5W	600lm	120lm/W	60°	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

# ICE<sup>™</sup>LAMP

## ICE<sup>™</sup> 5W GU10 DIMMABLE LED LAMP 4000K

### Specifications and Benefits

Ingress Protection Rating	IP20
Operating Temperature Range	-20°C / +40°C
Mounting Type	N/A
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium, PC
Finishing	White
Available accessories	N/A

### Photometric Specifications

Lumens	600lm
Efficiency	Up to 120lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<6
Beam Angle	60°
CRI	>80
Dimming Type	Dimmable
Distribution	Direct

### Technical Specifications

Wattage	5W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.5
Switching Cycles	>15,000
Lifetime Hours	L70 B20 25,000hrs L80 B20 15,000hrs
Energy Rating	E
Insulation Coverable	N/A
Inrush Current	9A

### Logistic Details

EAN / Barcode	3609640149451
Product Weight	53g
Product Dimensions (ODxH / LxWxH)	Ø50 x 57mm
Boxed Product Weight	70g
Boxed Product Dimensions (LxWxH)	51 x 51 x 62mm
Outer Carton Boxed Product Quantity	100 pcs
Outer Carton Dimensions (LxWxH)	170 x 595 x 290mm

