



ClearVu™

CLEARVU™ GU10 5W 38° DIMMABLE LED LAMP 3000K

- Cost effective and super reliable GU10 lamp range with advanced thermal management to control key component temperatures.
- Single Colour version with LEDchroic lens design with 38° beam angle imitates the appearance of halogen lamps and provides controlled, uniform light distribution with minimal glare.
- Designed and tested for suitable use in enclosed fire rated and insulation coverable lighting fixtures. Excellent dimming compatibility with all market common dimmers in Europe.

Code	Version	Colour	Watts	Lumens	lm/W	Beam	CRI
LA150563	Dimmable	3000K	5W	480lm	96lm/W	38°	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ClearVu™

CLEARVU™ GU10 5W 38° DIMMABLE LED LAMP 3000K

Specifications and Benefits

Ingress Protection Rating	IP20
Operating Temperature Range	-10°C / +30°C
Mounting Type	N/A
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium, PC
Cover Material	PC
Finishing	White
Available accessories	N/A

Technical Specifications

Wattage	5W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.7
Switching Cycles	>12,500
Lifetime Hours	L70 B20 25,000hrs L80 B20 15,000hrs
Energy Rating	F
Insulation Coverable	N/A
Inrush Current	2A

Photometric Specifications

Lumens	480lm
Efficiency	Up to 96lm/W
Colour Temperature	3000K
Light Colour Definition	Warm White
SDCM	<6
Beam Angle	38°
CRI	>80
Dimming Type	Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640150563
Product Weight	27g
Product Dimensions (ODxH / LxWxH)	Ø50 x 56mm
Recess Depth	55mm
Boxed Product Weight	43g
Boxed Product Dimensions (LxWxH)	51 x 51 x 62mm
Outer Carton Boxed Product Quantity	100 pcs
Outer Carton Dimensions (LxWxH)	280 x 280 x 280mm

