



VersiTile™

VERSITILE™ 27W 600 X 600MM IP65 UGR19 NON-DIMMABLE PANEL 4000K

- IP65 VersiTile LED BackLit panel with an efficiency of 120lm/W is the perfect choice for highly demanding environments such as healthcare, kitchens and commercial.
- IP65 rated front- and backside as well as metal grommet and valve enable a reliable and secure installation.
- PMMA lens technology with high transmission microprismatic and waterproof diffuser provides excellent glare control and high uniformity with an UGR19.
- Flicker-free IP65 rated LED driver pre-wired for simplified and fast installation.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
LP150280	Non-Dimmable	4000K	30W	3600lm	120lm/W	19	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

VersiTile™

VERSITILE™ 27W 600 X 600MM IP65 UGR19 NON-DIMMABLE PANEL 4000K

Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK02
Operating Temperature Range	-10°C / +40°C
Mounting Type	Surface mounted / Suspended
Positional Adjustment	Fixed
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	Polymer
Finishing	White

Technical Specifications

Wattage	30W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>10,000
Lifetime Hours	L70 B50 110,000hrs L80 B20 72,000hrs
Energy Rating	E
Insulation Coverable	NO

Photometric Specifications

Lumens	3600lm
Efficiency	Up to 120lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<3
Beam Angle	90°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640150280
Product Weight	1698g
Product Dimensions (ODxH / LxWxH)	595 x 595 x 34mm
Recess Depth	34mm
Boxed Product Weight	2420g
Boxed Product Dimensions (LxWxH)	665 x 620 x 45mm
Outer Carton Boxed Product Quantity	5 pcs
Outer Carton Dimensions (LxWxH)	630 x 235 x 685mm

