



LouvreCWS™

LOUVRE CSR™ REFLECTOR MODULE 15W 3CCT 3000K/3500/4000K WHITE

- Colour Switchable high-efficiency (up to 140lm/W) Modular LED Reflector Panel uses low glare effector technology to replicate the appearance of traditional direct/indirect luminaires.
- Full product modularity for maximum flexibility and product maintainance. Select individual components to customize your product according to your project requirements.
- High efficiency light modules, available in white, black and silver, with low glare reflector module significantly reduce glare and enhance visual comfort.
- Different Colour Finishes of Backplate and reflector module available for maximum flexibility in every application.

Code	Version	Colour	Watts	lm/W	UGR	CRI
LP158590	Non-Dimmable	3000 / 3500 / 4000K	15W	140lm/W	16	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

LouvreCWS™

LOUVRE CSR™ REFLECTOR MODULE 15W 3CCT 3000K/3500/4000K WHITE

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK08
Operating Temperature Range	-10°C / +45°C
Positional Adjustment	
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class III
Installation Location	Indoor
Body Material	Plastic
Cover Material	PET
Available accessories	· 0-10V Driver · Dali Driver

Technical Specifications

Wattage	15W
Nominal Voltage	220-Vac
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Insulation Coverable	NO

Photometric Specifications

Lumens	/ 2100 / lm
Efficiency	Up to 140lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<3
Beam Angle	80°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct / Indirect

Logistic Details

EAN / Barcode	3609640158590
Product Weight	130g
Product Dimensions (ODxH / LxWxH)	560 x 37.5 x 17mm
Boxed Product Weight	140g
Outer Carton Boxed Product Quantity	0 pcs
Outer Carton Dimensions (LxWxH)	0 x 0 x 0mm