



## EdgeLite™

### EDGE LIT™ IP54 LED PANEL MICROPRISMATIC UGR19 1200X300MM NON-DIMMABLE 4000K

- IP54 Edge-lit LED Panel design with optical pattern PMMA light guide engineered for even and uniform light distribution.
- Microprismatic diffuser provides excellent glare control with UGR <19.
- Low profile product height of only 10mm enables installations in 15 and 24mm t-bar ceilings as well as ceiling suspension, surface mount or recess mount in plasterboard.
- Flicker-free non-dimmable LED driver pre-wired for simplified and fast through-wiring installation. Safety cable according to EN60598 included.
- Edge-lit design and optical pattern light guide engineered for even light distribution.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
<b>LP158668</b>	Non-Dimmable	4000K	26W	3400lm	130lm/W	19	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

# EdgeLite™

## EDGE LIT™ IP54 LED PANEL MICROPRISMATIC UGR19 1200X300MM NON-DIMMABLE 4000K

### Specifications and Benefits

Ingress Protection Rating	IP54
IK Rating	IK07
Operating Temperature Range	-10°C / +40°C
Mounting Type	Recessed / Suspended
Positional Adjustment	Fixed
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PMMA
Finishing	White

### Technical Specifications

Wattage	26W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>80,000
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Insulation Coverable	NO
Inrush Current	25A

### Photometric Specifications

Lumens	3400lm
Efficiency	Up to 130lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<3
Beam Angle	110°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

### Logistic Details

EAN / Barcode	3609640158668
Product Weight	1500g
Product Dimensions (ODxH / LxWxH)	1195 x 595 x 10mm
Recess Depth	10mm
Boxed Product Weight	2250g
Boxed Product Dimensions (LxWxH)	375 x 1230 x 38mm
Outer Carton Boxed Product Quantity	6 pcs
Outer Carton Dimensions (LxWxH)	395 x 1245 x 250mm

