



BackLite™

BACKLITE™ 30W 3600LM 600 X 600 LED PANEL 4000K UGR19 PRISMATIC

- Eco LED Backlit Panel with optical pattern PMMA lenses engineered for even and uniform light distribution offer best value for money.
- Microprismatic diffuser provides excellent glare control with UGR<19.
- Suitable for installations in 15 and 24mm t-bar ceilings as well as ceiling suspension, surface mount or recess mount in plasterboard.
- Flicker-free non-dimmable LED driver pre-wired for simplified and fast installation. Safety cable according to EN60598 included.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
LP161125	Non-Dimmable	4000K	30W	3600lm	120lm/W	19	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

BackLite™

BACKLITE™ 30W 3600LM 600 X 600 LED PANEL 4000K UGR19 PRISMATIC

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK02
Operating Temperature Range	-10°C / +45°C
Mounting Type	Recessed
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium, Steel
Cover Material	PS
Available accessories	N/A

Technical Specifications

Wattage	30W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>30,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Insulation Coverable	NO
Inrush Current	25A

Photometric Specifications

Lumens	3600lm
Efficiency	Up to 120lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<4
Beam Angle	90°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640161125
Product Weight	1400g
Product Dimensions (ODxH / LxWxH)	595 x 595 x 32mm
Boxed Product Weight	1600g
Boxed Product Dimensions (LxWxH)	45 x 610 x 625mm
Outer Carton Boxed Product Quantity	5 pcs
Outer Carton Dimensions (LxWxH)	250 x 625 x 640mm