



**PATHWAY CSR™**  
**BOLLARD Ø120XH840MM**

- Modular Colour & Wattage Switchable IP65 Bollard anthracite black cast aluminium housing — the perfect choice for demanding commercial and public outdoor environments.
- Durable corrosion- and impact resistant housing with salt-spray protection, integrated driver, and IP68 junction box for reliable through-wiring. Bollard option with socket available.
- Interchangeable bollard heads with 360° beam angle and optical performance design deliver a very low ULR value reducing light pollution.
- Integrated remote control programmable Photocell or PIR sensor enables presence detection and daylight-harvesting control for enhanced energy savings
- Suitable for ambient temperature -20°C to +50°C.

Code	Version
<b>OD162214</b>	Other



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## PATHWAY CSR

### BOLLARD Ø120XH840MM

#### Specifications and Benefits

Operating Temperature Range	-20°C / +50°C
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class I
Installation Location	Outdoor
Body Material	Aluminium, PC
Available accessories	N/A

#### Photometric Specifications

Dimming Type	Other
--------------	-------

#### Logistic Details

EAN / Barcode	3609640162214
Product Weight	2140g
Product Dimensions (ODxH / LxWxH)	Ø120 x 840mm
Boxed Product Weight	2780g
Outer Carton Boxed Product Quantity	1 pcs
Outer Carton Dimensions (LxWxH)	890 x 170 x 175mm