



## PrysimCS™

### PRYSIMCS™ 42W ADJUSTABLE ALUMINIUM LED WALLWASHER 3000K/3500K/4000K

- Colour Switchable Adjustable Rectangular recessed Aluminium LED wallwasher designed to highlight displays and wall features in both indoor and outdoor applications. Perfect for applications that require high quality light output and superior colour rendering.
- Adjustable rectangular tilt rotation of 70° to adapt to changing point of sale environments. Producing up to 4300 lumens from 42W LED, it is the perfect replacement for metal halide.
- Colour Switchable between 3000K/3500K/4000K.
- Non-dimmable flicker-free driver pre-wired for ease of installation.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>RT149956</b>	Non-Dimmable	3000 / 3500 / 4000K	42W	3900-4300lm	Up to 102lm/W	90



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## PrysimCS™

### PRYSIMCS™ 42W ADJUSTABLE ALUMINIUM LED WALLWASHER 3000K/3500K/4000K

#### Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK04
Operating Temperature Range	-20°C / +45°C
Mounting Type	Recessed
Cutout Dimension	min: 220x130mm - max: N/ Amm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PC
Finishing	White
Available accessories	N/A

#### Technical Specifications

Wattage	42W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>100,000
Lifetime Hours	L70 B50 50,000hrs L80 B20 35,000hrs
Energy Rating	E
Insulation Coverable	NO

#### Photometric Specifications

Lumens	3900 / 4300 / 4300lm
Efficiency	Up to 102lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	100°
CRI	>90
Dimming Type	Non-Dimmable
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640149956
Product Weight	1770g
Product Dimensions (ODxH / LxWxH)	235 x 145 x 120mm
Recess Depth	117mm
Boxed Product Weight	1850g
Boxed Product Dimensions (LxWxH)	170 x 280 x 190mm
Outer Carton Boxed Product Quantity	6 pcs
Outer Carton Dimensions (LxWxH)	695 x 295 x 365mm

