



RIVO CWS™

RIVOCWS™ WATTAGE & COLOUR SWITCHABLE 11.5W-31W TRACK SPOTLIGHT 55° BEAM ANGLE WHITE FINISH

- Colour & Wattage Switchable Adjustable Three-Circuit Track LED Spotlight designed to deliver flexible, high-quality, and effective lighting for display surfaces.
- Integrated in-track driver ensures a compact, sleek body finish when installed in track systems. Plug-and-play light source design enables quick, easy maintenance at the end of product life.
- Colour & wattage Switchable with switch conveniently located on the track adapter allows simple adjustment of light output and colour temperature, even after installation.
- Flexible aiming with 350° horizontal rotation and 90° vertical tilt, ideal for adapting to changing retail or display environments.
- Interchangeable high-efficiency reflector supplied in 55° beam angle. Opional reflectors available in 18°, 24° and 38°

| Code | Version | Colour | Watts | Lumens | lm/W | CRI |
|-----------------|--------------|---------------------|----------------------|-------------|---------------|-----|
| RT154196 | Non-Dimmable | 3000 / 3500 / 4000K | 11.5 / 17 / 22 / 31W | 1400-3400lm | Up to 123lm/W | 90 |



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

RIVO CWS™

RIVOCWS™ WATTAGE & COLOUR SWITCHABLE 11.5W-31W TRACK SPOTLIGHT 55° BEAM ANGLE WHITE FINISH

Specifications and Benefits

| | |
|-----------------------------|----------------------|
| Ingress Protection Rating | IP20 |
| Operating Temperature Range | -10°C / +35°C |
| Mounting Type | 3-circuit track |
| Cutout Dimension | min: N/Amm - max: mm |
| Certification | CE |
| Protection Class | Class II |
| Installation Location | Indoor |
| Body Material | Aluminium |
| Cover Material | Aluminium |
| Available accessories | N/A |

Technical Specifications

| | |
|------------------|--|
| Wattage | 11,5/17/22/31 |
| Nominal Voltage | 220-240Vac |
| Frequency | 50/60Hz |
| Power Factor | >0.95 |
| Switching Cycles | >10,000 |
| Lifetime Hours | L70 B50 72,000hrs L80 B20 50,000hrs |
| Energy Rating | F |
| Inrush Current | 48A |

Photometric Specifications

| | |
|-------------------------|---|
| Lumens | 11.5W - /1400 / lm 17W - / 2100 / lm 22W - / 2700 / lm 31W - / 3400 / lm |
| Efficiency | Up to 123lm/W |
| Colour Temperature | 3000 / 3500 / 4000K |
| Light Colour Definition | Switchable White |
| SDCM | <3 |
| Beam Angle | 55° |
| CRI | >90 |
| Dimming Type | Non-Dimmable |
| Distribution | Direct |

Logistic Details

| | |
|-------------------------------------|-------------------|
| EAN / Barcode | 3609640154196 |
| Product Weight | 700g |
| Product Dimensions (ODxH / LxWxH) | Ø80 x 120mm |
| Boxed Product Weight | 740g |
| Boxed Product Dimensions (LxWxH) | 85 x 185 x 158mm |
| Outer Carton Boxed Product Quantity | 24 pcs |
| Outer Carton Dimensions (LxWxH) | 360 x 575 x 340mm |

