



ApexCWS™

APEXCWS™ 28/38W 36° RETAIL WALLWASHER BLACK 3CCT 3000/4000K/5700K

- Colour & Wattage Switchable adjustable recessed Aluminium LED wallwasher designed to highlight displays and wall features. Perfect for applications that require high quality light output and superior colour rendering (CRI90).
- Adjustable rotate and tilt angles to adapt to changing point of sales environments. Producing up to 3800 lumens from 38W LED, it is the perfect replacement for metal halide.
- Rotates 350° with a horizontal adjustment of 50°. Opaque Polycarbonate diffuser with 90° beam angle.
- Non-dimmable flicker-free driver pre-wired for ease of installation.

Code	Version	Colour	Watts	lm/W	CRI
RT154202	Non-Dimmable	3000 / 4000 / 5700K	28 / 38W	103lm/W	90



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ApexCWS™

APEXCWS™ 28/38W 36° RETAIL WALLWASHER BLACK 3CCT 3000/4000K/5700K

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK05
Operating Temperature Range	-20°C / +40°C
Cutout Dimension	min: 165mm - max: mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	Glass
Available accessories	N/A

Photometric Specifications

Lumens	28W - 2672 / 2900 / 2672lm 38W - 3550 / 3800 / 3550lm
Efficiency	Up to 103lm/W
Colour Temperature	3000 / 4000 / 5700K
Light Colour Definition	Switchable White
Beam Angle	90°
CRI	>90
Dimming Type	Non-Dimmable
Distribution	Direct

Technical Specifications

Wattage	28/38
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Switching Cycles	>8,000
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Insulation Coverable	NO

Logistic Details

EAN / Barcode	3609640154202
Product Weight	1006g
Product Dimensions (ODxH / LxWxH)	Ø195 x 135mm
Boxed Product Weight	1217g
Boxed Product Dimensions (LxWxH)	165 x 210 x 210mm
Outer Carton Boxed Product Quantity	12 pcs
Outer Carton Dimensions (LxWxH)	435 x 435 x 505mm

