



IzziWS Tilt™

IZZI™ TILT DOWNLIGHT WATTAGE SELECTABLE WITHOUT REFLECTOR 3000K BLACK FINISH

- Round recessed LED Tilt Spotlight designed to provide best qualitative and effective lighting on display surfaces with superior luminaire efficiency of up to 135 lm/W.
- Wattage switch located at the back of the product for simple adjustment of light output even after the initial store opening. External driver with loop in/loop out connector allow rapid toolfree installation through push-fit terminals.
- 30° horizontal and vertical adjustable to adapt to changing point of sales environments in stores.
- Interchangeable high-efficiency reflectors available as accessories in 24°, 36° and 52° beam angles as well as Low glare louver and Honeycomb cover.
- Plug and Play high colour rendering COB (CRI95) enables product maintenance when reaching the end of product life.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
RT158026	Non-Dimmable	3000K	10 / 16 / 23W	1250-2900lm	Up to 128lm/W	95



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

IzziWS Tilt™

IZZI™ TILT DOWNLIGHT WATTAGE SELECTABLE WITHOUT REFLECTOR 3000K BLACK FINISH

Specifications and Benefits

Ingress Protection Rating	IP20
Operating Temperature Range	-10°C / +45°C
Mounting Type	Recessed
Positional Adjustment	Rotatable
Cutout Dimension	min: 100mm - max: N/Amm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	Glass
Finishing	Black
Available accessories	· RT157968 - 24° Reflector · RT357975 - 36° Reflector

Technical Specifications

Wattage	10/16/23
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>100,000
Lifetime Hours	L70 B50 90,000hrs L80 B20 60,000hrs
Insulation Coverable	NO
Inrush Current	8.76A

Photometric Specifications

Lumens	10W 1250lm 16W 2050lm 23W 2900lm
Efficiency	Up to 128lm/W
Colour Temperature	3000K
Light Colour Definition	Warm White
SDCM	<4
CRI	>95
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640158026
Product Weight	700g
Product Dimensions (ODxH / LxWxH)	Ø115 x 115mm
Recess Depth	115mm
Boxed Product Weight	895g
Outer Carton Boxed Product Quantity	0 pcs
Outer Carton Dimensions (LxWxH)	0 x 0 x 0mm

