




LEDlineTM COB

LEDLINETM IP67 COB 4.8W 24V SINGLE COLOUR FLEXIBLE STRIP 3000K

- Spotless COB IP67 Single Colour LED Strip delivers consistent, even light output with no dark spots ensuring perfectly illuminated spaces.
- Ideal for continuous-line applications with reflective surfaces or clear sightlines of the luminaire without the need for frosted diffuser profiles.
- Flexible installation with cut points every 20.8mm.
- Beam angle of 150° and 384 LEDs per metre.
- Connect individual lengths in parallel for runs longer than 5 metres.

Code	Version	Colour	Watts	Lumens	CRI
ST161620	Other	3000K	4.8W	390lm	90



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

LEDlineTM COB

LEDLINETM IP67 COB 4.8W 24V SINGLE COLOUR FLEXIBLE STRIP 3000K

Specifications and Benefits

Ingress Protection Rating	IP67
Operating Temperature Range	-20°C / +45°C
Mounting Type	Surface mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class III
Installation Location	Indoor / Outdoor
Body Material	Other
Available accessories	N/A

Photometric Specifications

Lumens	390lm
Colour Temperature	3000K
Light Colour Definition	Warm White
Beam Angle	150°
CRI	>90
Dimming Type	Other
Distribution	Direct

Technical Specifications

Wattage	4.8W
Nominal Voltage	24-24Vac
Power Factor	>1
Lifetime Hours	L70 B50 72,000hrs L80 B20 50,000hrs
Energy Rating	G
Insulation Coverable	NO

Logistic Details

EAN / Barcode	3609640161620
Product Weight	350g
Product Dimensions (ODxH / LxWxH)	5000 x 10 x 4mm
Boxed Product Weight	350g
Boxed Product Dimensions (LxWxH)	270 x 260 x 12mm
Outer Carton Boxed Product Quantity	40 pcs
Outer Carton Dimensions (LxWxH)	540 x 450 x 265mm