



LEDline™

SMD IP67 4.8W 24V SINGLE COLOUR FLEXIBLE STRIP 3000K

- SMD Single Colour LED Strip delivers the ideal balance of cost and performance. Supplied on a 5 m reel, complete with installation cable.
- Cost-effective solution for general lighting applications. Perfect in combination with frosted diffuser profiles for smooth, uniform illumination.
- Flexible installation with cut points every 20.8mm.
- Beam angle of 150° and 60 LEDs per metre.
- Connect individual lengths in parallel for runs longer than 5 metres.

Code	Version	Colour	Watts	Lumens	CRI
ST162283	Other	3000K	4.8W	470lm	90



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

LEDline™

SMD IP67 4.8W 24V SINGLE COLOUR FLEXIBLE STRIP 3000K

Specifications and Benefits

Ingress Protection Rating	IP67
Operating Temperature Range	-20°C / +45°C
Mounting Type	Surface mounted
Cutout Dimension	min: N/Amm - max: mm
Certification	CE
Protection Class	Class III
Installation Location	Indoor / Outdoor
Body Material	Other
Available accessories	N/A

Photometric Specifications

Lumens	470lm
Colour Temperature	3000K
Light Colour Definition	Warm White
Beam Angle	120°
CRI	>90
Dimming Type	Other
Distribution	Direct

Technical Specifications

Wattage	4.8W
Nominal Voltage	24-24Vac
Lifetime Hours	L70 B50 60,000hrs L80 B20 50,000hrs
Energy Rating	F
Insulation Coverable	NO

Logistic Details

EAN / Barcode	3609640162283
Product Weight	375g
Product Dimensions (ODxH / LxWxH)	5000 x 10 x 4mm
Boxed Product Weight	400g
Boxed Product Dimensions (LxWxH)	270 x 260 x 5mm
Outer Carton Boxed Product Quantity	40 pcs
Outer Carton Dimensions (LxWxH)	540 x 450 x 265mm